

§ 173.225 Packaging requirements and other provisions for organic peroxides.

(a) *General.* When the §172.101 table specifies that an organic peroxide must be packaged under this section, the organic peroxide must be packaged and offered for transportation in accordance with the provisions of this section. Each packaging must conform to the general requirements of subpart B of part 173 and to the applicable requirements of part 178 of this subchapter. Non-bulk packagings must meet Packing Group II performance levels. To avoid unnecessary confinement, metallic non-bulk packagings meeting Packing Group I are not authorized. No used material, other than production residues or regrind from the same production process, may be used in plastic packagings. Organic peroxides that require temperature control are subject to the provisions of §173.21(f). When an IBC or bulk packaging is authorized and meets the requirements of paragraph (f) or (h) of this section, respectively, lower control temperatures than those specified for non-bulk packaging may be required. An organic peroxide not identified in paragraph (c), (e), or (g) of this section by technical name, or not assigned to a generic type in accordance with the provisions in paragraph (b)(3) of this section, must conform to the provisions of paragraph (c) of §173.128.

(b) *New organic peroxides, formulations and samples.* (1) Except as provided for samples in paragraph (b)(2) of this section, no person may offer for transportation an organic peroxide that is not identified by technical name in the Organic Peroxides Table, Organic Peroxide IBC Table, or the Organic Peroxide Portable Tank Table of this section, or a formulation of one or more organic peroxides that are identified by technical name in one of those tables, unless the organic peroxide is assigned a generic type and shipping description and is approved by the Associate Administrator under the provisions of §173.128(d) of this subchapter.

(2) *Samples.* Samples of new organic peroxides or new formulations of organic peroxides identified in the Organic Peroxides Table in paragraph (c) of this section, for which complete test data are not available, and that are to be transported for further testing or product evaluation, may be assigned an appropriate shipping description for organic peroxide Type C, packaged and offered for transportation, under the following conditions:

(i) Data available to the person offering the material for transportation must indicate that the sample would pose a level of hazard no greater than that of an organic peroxide Type B and that the control temperature, if any, is sufficiently low to prevent any dangerous decomposition and sufficiently high to prevent any dangerous phase separation;

(ii) The sample must be packaged in accordance with packing method OP2, for a liquid or solid, respectively;

(iii) Packages of the organic peroxide may be offered for transportation and transported in a quantity not to exceed 10 kg (22 pounds) per transport vehicle; and

(iv) One of the following shipping descriptions must be assigned:

(A) Organic peroxide Type C, liquid, 5.2, UN 3103;

(B) Organic peroxide Type C, solid, 5.2, UN 3104;

(C) Organic peroxide Type C, liquid, temperature controlled, 5.2, UN 3113; or

(D) Organic peroxide Type C, solid, temperature controlled, 5.2, UN 3114.

(3) *Mixtures.* Mixtures of organic peroxides individually identified in the Organic Peroxides Table in paragraph (c) of this section may be classified as the same type of organic peroxide as that of the most dangerous component and be transported under the conditions for transportation given for this type. If the stable components form a thermally less stable mixture, the SADT of the mixture must be determined and the new control and emergency temperature derived under the provisions of §173.21(f).

(c) *Organic peroxides table.* The following Organic Peroxides Table specifies by technical name those organic peroxides that are authorized for transportation and not subject to the approval provisions of §173.128 of this part. An organic peroxide identified by technical name in the following table is authorized for transportation only if it conforms to all applicable provisions of the table. The column headings of the Organic Peroxides Table are as follows:

(1) *Technical name.* The first column specifies the technical name.

(2) *ID number.* The second column specifies the identification (ID) number which is used to identify the proper shipping name in the §172.101 table. The word “EXEMPT” appearing in the column denotes that the material is not regulated as an organic peroxide.

(3) *Concentration of organic peroxide.* The third column specifies concentration (mass percent) limitations, if any, in mixtures or solutions for the organic peroxide. Limitations are given as minimums, maximums, or a range, as appropriate. A range includes the lower and upper limits (*i.e.* , “53–100” means from, and including, 53% to, and including 100%). See introductory paragraph of §172.203 (k) of this subchapter for additional description requirements for an organic peroxide that may qualify for more than one generic listing, depending on its concentration.

(4) *Concentration of diluents.* The fourth column specifies the type and concentration (mass percent) of diluent or inert solid, when required. Other types and concentrations of diluents may be used if approved by the Associate Administrator.

(i) The required mass percent of “Diluent type A” is specified in column 4a. A diluent type A is an organic liquid that does not detrimentally affect the thermal stability or increase the hazard of the organic peroxide and with a boiling point not less than 150 °C at atmospheric pressure. Type A diluents may be used for desensitizing all organic peroxides.

(ii) The required mass percent of “Diluent type B” is specified in column 4b. A diluent type B is an organic liquid which is compatible with the organic peroxide and which has a boiling point, at atmospheric pressure, of less than 150 °C (302 °F) but at least 60 °C (140 °F), and a flash point greater than 5 °C (41 °F). Type B diluents may be used for desensitizing all organic peroxides, when specified in the organic peroxide tables, provided that the boiling point is at least 60 °C (140 °F) above the SADT of the peroxide in a 50 kg (110 lbs) package. A type A diluent may be used to replace a type B diluent in equal concentration.

(iii) The required mass percent of “Inert solid” is specified in column 4c. An inert solid is a solid that does not detrimentally affect the thermal stability or hazard of the organic peroxide.

(5) *Concentration of water.* Column 5 specifies, in mass percent, the minimum amount of water, if any, which must be in formulation.

(6) *Packing method.* Column 6 specifies the highest packing method (largest packaging capacity) authorized for the organic peroxide. Lower numbered packing methods (smaller packaging capacities) are also authorized. For example, if OP3 is specified, then OP2 and OP1 are also authorized. The Table of Packing Methods in paragraph (d) of this section defines the non-bulk packing methods.

(7) *Temperatures.* Column 7a specifies the control temperature. Column 7b specifies the emergency temperature. Temperatures are specified only when temperature controls are required. (See §173.21(f)).

(8) *Notes.* Column 8 specifies other applicable provisions, as set forth in notes following the table.

Organic Peroxide Table

Technical name	ID number	Concentration (mass %)	Diluent (mass %)			Water (mass %)	Packing method	Temperature (°C)		Notes
			A	B	I			Control	Emergency	
(1)	(2)	(3)	(4a)	(4b)	(4c)	(5)	(6)	(7a)	(7b)	(8)
Acetyl acetone peroxide	UN3105	≤42	≥48			≥8	OP7			2
Acetyl acetone peroxide [as a paste]	UN3106	≤32					OP7			21
Acetyl cyclohexanesulfonyl peroxide	UN3112	≤82				≥12	OP4	-10	0	
Acetyl cyclohexanesulfonyl peroxide	UN3115	≤32		≥68			OP7	-10	0	
tert-Amyl hydroperoxide	UN3107	≤88	≥6			≥6	OP8			
tert-Amyl peroxyacetate	UN3105	≤62	≥38				OP7			

tert-Amyl peroxybenzoate	UN3103	≤100				OP5			
tert-Amyl peroxy-2-ethylhexanoate	UN3115	≤100				OP7	+20	+25	
tert-Amyl peroxy-2-ethylhexyl carbonate	UN3105	≤100				OP7			
tert-Amyl peroxy isopropyl carbonate	UN3103	≤77	≥23			OP5			
tert-Amyl peroxyneodecanoate	UN3115	≤77		≥23		OP7	0	+10	
tert-Amyl peroxy-pivalate	UN3113	≤77		≥23		OP5	+10	+15	
tert-Amyl peroxy-3,5,5-trimethylhexanoate	UN3101	≤100				OP5			
tert-Butyl cumyl peroxide	UN3107	>42–100				OP8			9
tert-Butyl cumyl peroxide	UN3108	≤52			≥48	OP8			9
n-Butyl-4,4-di-(tert-butylperoxy) valerate	UN3103	>52–100				OP5			
n-Butyl-4,4-di-(tert-butylperoxy) valerate	UN3108	≤52			≥48	OP8			
tert-Butyl hydroperoxide	UN3103	>79–90				OP5			13
tert-Butyl hydroperoxide	UN3105	≤80	≥20			OP7			4, 13
tert-Butyl hydroperoxide	UN3107	≤79				OP8	>14		13, 16
tert-Butyl hydroperoxide	UN3109	≤72				OP8	≥28		13
tert-Butyl hydroperoxide [and] Di-tert-butylperoxide	UN3103	<82+>9				OP5	≥7		13
tert-Butyl monoperoxymaleate	UN3102	>52–100				OP5			
tert-Butyl monoperoxymaleate	UN3103	≤52	≥48			OP6			
tert-Butyl monoperoxymaleate	UN3108	≤52			≥48	OP8			
tert-Butyl monoperoxymaleate [as a paste]	UN3108	≤52				OP8			
tert-Butyl peroxyacetate	UN3101	>52–77	≥23			OP5			
tert-Butyl peroxyacetate	UN3103	>32–52	≥48			OP6			
tert-Butyl peroxyacetate	UN3109	≤32		≥68		OP8			
tert-Butyl peroxybenzoate	UN3103	>77–100				OP5			
tert-Butyl peroxybenzoate	UN3105	>52–77	≥23			OP7			1
tert-Butyl peroxybenzoate	UN3106	≤52			≥48	OP7			
tert-Butyl peroxybutyl fumarate	UN3105	≤52	≥48			OP7			
tert-Butyl peroxy-crotonate	UN3105	≤77	≥23			OP7			
tert-Butyl peroxydiethylacetate	UN3113	≤100				OP5	+20	+25	
tert-Butyl peroxy-2-ethylhexanoate	UN3113	>52–100				OP6	+20	+25	
tert-Butyl peroxy-2-ethylhexanoate	UN3117	>32–52		≥48		OP8	+30	+35	
tert-Butyl peroxy-2-ethylhexanoate	UN3118	≤52			≥48	OP8	+20	+25	
tert-Butyl peroxy-2-ethylhexanoate	UN3119	≤32		≥68		OP8	+40	+45	

tert-Butyl peroxy-2-ethylhexanoate [and] 2,2-di-(tert-Butylperoxy)butane	UN3106	≤12+≤14	≥14	≥60	OP7		
tert-Butyl peroxy-2-ethylhexanoate [and] 2,2-di-(tert-Butylperoxy)butane	UN3115	≤31+≤36		≥33	OP7	+35	+40
tert-Butyl peroxy-2-ethylhexylcarbonate	UN3105	≤100			OP7		
tert-Butyl peroxyisobutyrate	UN3111	>52-77		≥23	OP5	+15	+20
tert-Butyl peroxyisobutyrate	UN3115	≤52		≥48	OP7	+15	+20
tert-Butylperoxy isopropylcarbonate	UN3103	≤77	≥23		OP5		
1-(2-tert-Butylperoxy isopropyl)-3-isopropenylbenzene	UN3105	≤77	≥23		OP7		
1-(2-tert-Butylperoxy isopropyl)-3-isopropenylbenzene	UN3108	≤42		≥58	OP8		
tert-Butyl peroxy-2-methylbenzoate	UN3103	≤100			OP5		
tert-Butyl peroxyneodecanoate	UN3115	>77-100			OP7	-5	+5
tert-Butyl peroxyneodecanoate	UN3115	≤77	≥23		OP7	0	+10
tert-Butyl peroxyneodecanoate [as a stable dispersion in water]	UN3119	≤52			OP8	0	+10
tert-Butyl peroxyneodecanoate [as a stable dispersion in water (frozen)]	UN3118	≤42			OP8	0	+10
tert-Butyl peroxyneodecanoate	UN3119	≤32	≥68		OP8	0	+10
tert-Butyl peroxyneoheptanoate	UN3115	≤77	≥23		OP7	0	+10
tert-Butyl peroxyneoheptanoate [as a stable dispersion in water]	UN3117	≤42			OP8	0	+10
tert-Butyl peroxy-pivalate	UN3113	>67-77	≥23		OP5	0	+10
tert-Butyl peroxy-pivalate	UN3115	>27-67		≥33	OP7	0	+10
tert-Butyl peroxy-pivalate	UN3119	≤27		≥73	OP8	+30	+35
tert-Butylperoxy stearylcarbonate	UN3106	≤100			OP7		
tert-Butyl peroxy-3,5,5-trimethylhexanoate	UN3105	>32-100			OP7		
tert-Butyl peroxy-3,5,5-trimethylhexanoate	UN3109	≤32		≥68	OP8		
3-Chloroperoxybenzoic acid	UN3102	>57-86		≥14	OP1		
3-Chloroperoxybenzoic acid	UN3106	≤57		≥3	≥40	OP7	
3-Chloroperoxybenzoic acid	UN3106	≤77		≥6	≥17	OP7	
Cumyl hydroperoxide	UN3107	>90-98	≤10		OP8		13
Cumyl hydroperoxide	UN3109	≤90	≥10		OP8		13, 15
Cumyl peroxyneodecanoate	UN3115	≤77		≥23	OP7	-10	0

Cumyl peroxyneodecanoate [as a stable dispersion in water]	UN3119	≤52			OP8	-10	0	
Cumyl peroxyneoheptanoate	UN3115	≤77	≥23		OP7	-10	0	
Cumyl peroxy-pivalate	UN3115	≤77		≥23	OP7	-5	+5	
Cyclohexanone peroxide(s)	UN3104	≤91			≥9	OP6		13
Cyclohexanone peroxide(s)	UN3105	≤72	≥28		OP7			5
Cyclohexanone peroxide(s) [as a paste]	UN3106	≤72			OP7			5, 21
Cyclohexanone peroxide(s)	Exempt	≤32		≥68	Exempt			
Diacetone alcohol peroxides	UN3115	≤57	≥26	≥8	OP7	+40	+45	5
Diacetyl peroxide	UN3115	≤27	≥73		OP7	+20	+25	8,13
Di-tert-amyl peroxide	UN3107	≤100			OP8			
1,1-Di-(tert-amylperoxy) cyclohexane	UN3103	≤82	≥18		OP6			
Dibenzoyl peroxide	UN3102	>51-100		≤48	OP2			3
Dibenzoyl peroxide	UN3102	>77-94		≥6	OP4			3
Dibenzoyl peroxide	UN3104	≤77		≥23	OP6			
Dibenzoyl peroxide	UN3106	≤62	≥28	≥10	OP7			
Dibenzoyl peroxide [as a paste]	UN3106	>52-62			OP7			21
Dibenzoyl peroxide	UN3106	>35-52	≥48		OP7			
Dibenzoyl peroxide	UN3107	>36-42	≥18	≤40	OP8			
Dibenzoyl peroxide [as a paste]	UN3108	≤56.5		≥15	OP8			
Dibenzoyl peroxide [as a paste]	UN3108	≤52			OP8			21
Dibenzoyl peroxide [as a stable dispersion in water]	UN3109	≤42			OP8			
Dibenzoyl peroxide	Exempt	≤35	≥65		Exempt			
Di-(4-tert-butylcyclohexyl) peroxydicarbonate	UN3114	≤100			OP6	+30	+35	
Di-(4-tert-butylcyclohexyl) peroxydicarbonate [as a stable dispersion in water]	UN3119	≤42			OP8	+30	+35	
Di-tert-butyl peroxide	UN3107	>52-100			OP8			
Di-tert-butyl peroxide	UN3109	≤52	≥48		OP8			24
Di-tert-butyl peroxyazolate	UN3105	≤52	≥48		OP7			
2,2-Di-(tert-butylperoxy)butane	UN3103	≤52	≥48		OP6			
1,6-Di-(tert-butylperoxycarbonyloxy)hexane	UN3103	≤72	≥28		OP5			
1,1-Di-(tert-butylperoxy) cyclohexane	UN3101	>80-100			OP5			
1,1-Di-(tert-butylperoxy) cyclohexane	UN3103	>52-80	≥20		OP5			

1,1-Di-(tert-butylperoxy) cyclohexane	UN3105	>42–52	≥48			OP7			
1,1-Di-(tert-butylperoxy) cyclohexane	UN3106	≤42	≥13		≥45	OP7			
1,1-Di-(tert-butylperoxy) cyclohexane	UN3107	≤27	≥25			OP8			22
1,1-Di-(tert-butylperoxy) cyclohexane	UN3109	≤42	≥58			OP8			
1,1-Di-(tert-butylperoxy) cyclohexane	UN3109	≤25	≥25	≥50		OP8			
1,1-Di-(tert-butylperoxy) cyclohexane	UN3109	≤13	≥13	≥74		OP8			
Di-n-butyl peroxydicarbonate	UN3115	>27–52		≥48		OP7	-15	-5	
Di-n-butyl peroxydicarbonate	UN3117	≤27		≥73		OP8	-10	0	
Di-n-butyl peroxydicarbonate [as a stable dispersion in water (frozen)]	UN3118	≤42				OP8	-15	-5	
Di-sec-butyl peroxydicarbonate	UN3113	>52–100				OP4	-20	-10	6
Di-sec-butyl peroxydicarbonate	UN3115	≤52		≥48		OP7	-15	-5	
Di-(2-tert-butylperoxyisopropyl) benzene(s)	UN3106	>42–100			≤57	OP7			1, 9
Di-(2-tert-butylperoxyisopropyl) benzene(s)	Exempt	≤42			≥58	Exempt			
Di-(tert-butylperoxy)phthalate	UN3105	>42–52	≥48			OP7			
Di-(tert-butylperoxy)phthalate [as a paste]	UN3106	≤52				OP7			21
Di-(tert-butylperoxy)phthalate	UN3107	≤42	≥58			OP8			
2,2-Di-(tert-butylperoxy)propane	UN3105	≤52	≥48			OP7			
2,2-Di-(tert-butylperoxy)propane	UN3106	≤42	≥13		≥45	OP7			
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane	UN3101	>90–100				OP5			
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane	UN3103	>57–90	≥10			OP5			
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane	UN3103	≤77		≥23		OP5			
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane	UN3110	≤57			≥43	OP8			
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane	UN3107	≤57	≥43			OP8			
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane	UN3107	≤32	≥26	≥42		OP8			
Dicetyl peroxydicarbonate	UN3116	≤100				OP7	+30	+35	
Dicetyl peroxydicarbonate [as a stable dispersion in water]	UN3119	≤42				OP8	+30	+35	
Di-4-chlorobenzoyl peroxide	UN3102	≤77			≥23	OP5			

Di-4-chlorobenzoyl peroxide [as a paste]	UN3106	≤52			OP7			21
Di-4-chlorobenzoyl peroxide	Exempt	≤32	≥68		Exempt			
Dicumyl peroxide	UN3110	>52–100	≤48		OP8			9
Dicumyl peroxide	Exempt	≤52	≥48		Exempt			
Dicyclohexyl peroxydicarbonate	UN3112	>91–100			OP3	+10	+15	
Dicyclohexyl peroxydicarbonate	UN3114	≤91		≥9	OP5	+10	+15	
Dicyclohexyl peroxydicarbonate [as a stable dispersion in water]	UN3119	≤42			OP8	+15	+20	
Didecanoyl peroxide	UN3114	≤100			OP6	+30	+35	
2,2-Di-(4,4-di(tert-butylperoxy)cyclohexyl)propane	UN3106	≤42	≥58		OP7			
2,2-Di-(4,4-di(tert-butylperoxy)cyclohexyl)propane	UN3107	≤22	≥78		OP8			
Di-2,4-dichlorobenzoyl peroxide	UN3102	≤77		≥23	OP5			
Di-2,4-dichlorobenzoyl peroxide [as a paste with silicone oil]	UN3106	≤52			OP7			
Di-(2-ethoxyethyl) peroxydicarbonate	UN3115	≤52	≥48		OP7	-10	0	
Di-(2-ethylhexyl) peroxydicarbonate	UN3113	>77–100			OP5	-20	-10	
Di-(2-ethylhexyl) peroxydicarbonate	UN3115	≤77	≥23		OP7	-15	-5	
Di-(2-ethylhexyl) peroxydicarbonate [as a stable dispersion in water]	UN3117	≤62			OP8	-15	-5	
Di-(2-ethylhexyl) peroxydicarbonate [as a stable dispersion in water]	UN3119	≤52			OP8	-15	-5	
Di-(2-ethylhexyl) peroxydicarbonate [as a stable dispersion in water (frozen)]	UN3120	≤52			OP8	-15	-5	
2,2-Dihydroperoxypropane	UN3102	≤27	≥73		OP5			
Di-(1-hydroxycyclohexyl)peroxide	UN3106	≤100			OP7			
Diisobutyl peroxide	UN3111	>32–52	≥48		OP5	-20	-10	
Diisobutyl peroxide	UN3115	≤32	≥68		OP7	-20	-10	
Diisopropylbenzene dihydroperoxide	UN3106	≤82	≥5	≥5	OP7			17
Diisopropyl peroxydicarbonate	UN3112	>52–100			OP2	-15	-5	
Diisopropyl peroxydicarbonate	UN3115	≤52	≥48		OP7	-20	-10	
Diisopropyl peroxydicarbonate	UN3115	≤28	≥72		OP7	-15	-5	
Dilauroyl peroxide	UN3106	≤100			OP7			

Dilauroyl peroxide [as a stable dispersion in water]	UN3109	≤42			OP8		
Di-(3-methoxybutyl) peroxydicarbonate	UN3115	≤52	≥48		OP7	-5	+5
Di-(2-methylbenzoyl)peroxide	UN3112	≤87		≥13	OP5	+30	+35
Di-(4-methylbenzoyl)peroxide [as a paste with silicone oil]	UN3106	≤52			OP7		
Di-(3-methylbenzoyl) peroxide + Benzoyl (3-methylbenzoyl) peroxide + Dibenzoyl peroxide	UN3115	≤20+≤18+≤4	≥58		OP7	+35	+40
2,5-Dimethyl-2,5-di-(benzoylperoxy)hexane	UN3102	>82-100			OP5		
2,5-Dimethyl-2,5-di-(benzoylperoxy)hexane	UN3106	≤82		≥18	OP7		
2,5-Dimethyl-2,5-di-(benzoylperoxy)hexane	UN3104	≤82		≥18	OP5		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexane	UN3105	>52-100			OP7		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexane	UN3108	≤77		≥23	OP8		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexane	UN3109	≤52	≥48		OP8		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexane [as a paste]	UN3108	≤47			OP8		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexyne-3	UN3101	>86-100			OP5		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexyne-3	UN3103	>52-86	≥14		OP5		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexyne-3	UN3106	≤52		≥48	OP7		
2,5-Dimethyl-2,5-di-(2-ethylhexanoylperoxy)hexane	UN3113	≤100			OP5	+20	+25
2,5-Dimethyl-2,5-dihydroperoxyhexane	UN3104	≤82		≥18	OP6		
2,5-Dimethyl-2,5-di-(3,5,5-trimethylhexanoylperoxy)hexane	UN3105	≤77	≥23		OP7		
1,1-Dimethyl-3-hydroxybutylperoxyneoheptanoate	UN3117	≤52	≥48		OP8	0	+10
Dimyristyl peroxydicarbonate	UN3116	≤100			OP7	+20	+25
Dimyristyl peroxydicarbonate [as a stable dispersion in water]	UN3119	≤42			OP8	+20	+25
Di-(2-neodecanoylperoxyisopropyl) benzene	UN3115	≤52	≥48		OP7	-10	0
Di-n-nonanoyl peroxide	UN3116	≤100			OP7	0	+10

Di-n-octanoyl peroxide	UN3114	≤100				OP5	+10	+15	
Di-(2-phenoxyethyl) peroxydicarbonate	UN3102	>85-100				OP5			
Di-(2-phenoxyethyl) peroxydicarbonate	UN3106	≤85			≥15	OP7			
Dipropionyl peroxide	UN3117	≤27		≥73		OP8	+15	+20	
Di-n-propyl peroxydicarbonate	UN3113	≤100				OP3	-25	-15	
Di-n-propyl peroxydicarbonate	UN3113	≤77		≥23		OP5	-20	-10	
Disuccinic acid peroxide	UN3102	>72-100				OP4			18
Disuccinic acid peroxide	UN3116	≤72			≥28	OP7	+10	+15	
Di-(3,5,5-trimethylhexanoyl) peroxide	UN3115	>38-82	≥18			OP7	0	+10	
Di-(3,5,5-trimethylhexanoyl) peroxide [as a stable dispersion in water]	UN3119	≤52				OP8	+10	+15	
Di-(3,5,5-trimethylhexanoyl) peroxide	UN3119	≤38	≥62			OP8	+20	+25	
Ethyl 3,3-di-(tert-amylperoxy) butyrate	UN3105	≤67	≥33			OP7			
Ethyl 3,3-di-(tert-butylperoxy) butyrate	UN3103	>77-100				OP5			
Ethyl 3,3-di-(tert-butylperoxy) butyrate	UN3105	≤77	≥23			OP7			
Ethyl 3,3-di-(tert-butylperoxy) butyrate	UN3106	≤52		≥48		OP7			
1-(2-ethylhexanoylperoxy)-1,3-Dimethylbutyl peroxy-pivalate	UN3115	≤52	≥45	≥10		OP7	-20	-10	
tert-Hexyl peroxyneodecanoate	UN3115	≤71	≥29			OP7	0	+10	
tert-Hexyl peroxy-pivalate	UN3115	≤72		≥28		OP7	+10	+15	
Isopropyl sec-butyl peroxydicarbonat +Di-sec-butyl peroxydicarbonate+Di-isopropyl peroxydicarbonate	UN3111	≤52+≤28+≤22				OP5	-20	-10	
Isopropyl sec-butyl peroxydicarbonate+Di-sec-butyl peroxydicarbonate+Di-isopropyl peroxydicarbonate	UN3115	≤32+≤15-18 +≤12-15	≥38			OP7	-20	-10	
Isopropylcumyl hydroperoxide	UN3109	≤72	≥28			OP8			13
p-Menthyl hydroperoxide	UN3105	> 72-100				OP7			13
p-Menthyl hydroperoxide	UN3109	≤72	≥28			OP8			
Methylcyclohexanone peroxide(s)	UN3115	≤67		≥33		OP7	+35	+40	
Methyl ethyl ketone peroxide(s)	UN3101	≤52	≥48			OP5			5, 13
Methyl ethyl ketone peroxide(s)	UN3105	≤45	≥55			OP7			5
Methyl ethyl ketone peroxide(s)	UN3107	≤40	≥60			OP8			7

Methyl isobutyl ketone peroxide(s)	UN3105	≤62	≥19		OP7				5, 23
Organic peroxide, liquid, sample	UN3103				OP2				12
Organic peroxide, liquid, sample, temperature controlled	UN3113				OP2				12
Organic peroxide, solid, sample	UN3104				OP2				12
Organic peroxide, solid, sample, temperature controlled	UN3114				OP2				12
Peroxyacetic acid, type D, stabilized	UN3105	≤43			OP7				13, 20
Peroxyacetic acid, type E, stabilized	UN3107	≤43			OP8				13, 20
Peroxyacetic acid, type F, stabilized	UN3109	≤43			OP8				13, 20, 28
Peroxyacetic acid or peracetic acid [with not more than 7% hydrogen peroxide]	UN3107	≤36			≥15	OP8			13, 20, 28
Peroxyacetic acid or peracetic acid [with not more than 20% hydrogen peroxide]	Exempt	≤6			≥60	Exempt			28
Peroxyacetic acid or peracetic acid [with not more than 26% hydrogen peroxide]	UN3109	≤17				OP8			13, 20, 28
Peroxyauric acid	UN3118	≤100				OP8	+35	+40	
Pinanyl hydroperoxide	UN3105	>56–100				OP7			13
Pinanyl hydroperoxide	UN3109	≤56	≥44			OP8			
Polyether poly-tert-butylperoxycarbonate	UN3107	≤52		≥48		OP8			
Tetrahydronaphthyl hydroperoxide	UN3106	≤100				OP7			
1,1,3,3-Tetramethylbutyl hydroperoxide	UN3105	≤100				OP7			
1,1,3,3-Tetramethylbutyl peroxy-2-ethylhexanoate	UN3115	≤100				OP7	+15	+20	
1,1,3,3-Tetramethylbutyl peroxyneodecanoate	UN3115	≤72		≥28		OP7	-5	+5	
1,1,3,3-Tetramethylbutyl peroxyneodecanoate [as a stable dispersion in water]	UN3119	≤52				OP8	-5	+5	
1,1,3,3-tetramethylbutyl peroxy-pivalate	UN3115	≤77	≥23			OP7	0	+10	
3,6,9-Triethyl-3,6,9-trimethyl-1,4,7-triperoxonane	UN3105	≤42	≥58			OP7			26

Notes

1. For domestic shipments, OP8 is authorized.

2. Available oxygen must be <4.7%.
3. For concentrations <80% OP5 is allowed. For concentrations of at least 80% but <85%, OP4 is allowed. For concentrations of at least 85%, maximum package size is OP2.
4. The diluent may be replaced by di-tert-butyl peroxide.
5. Available oxygen must be $\leq 9\%$ with or without water.
6. For domestic shipments, OP5 is authorized.
7. Available oxygen must be $\leq 8.2\%$ with or without water.
8. Only non-metallic packagings are authorized.
9. For domestic shipments this material maybe transported under the provisions of paragraph (h)(3)(xii) of this section.
10. [Reserved]
11. [Reserved]
12. Samples may only be offered for transportation under the provisions of paragraph (b)(2) of this section.
13. "Corrosive" subsidiary risk label is required.
14. [Reserved]
15. No "Corrosive" subsidiary risk label is required for concentrations below 80%.
16. With <6% di-tert-butyl peroxide.
17. With $\leq 8\%$ 1-isopropylhydroperoxy-4-isopropylhydroxybenzene.
18. Addition of water to this organic peroxide will decrease its thermal stability.
19. [Reserved]
20. Mixtures with hydrogen peroxide, water and acid(s).
21. With diluent type A, with or without water.
22. With $\geq 36\%$ diluent type A by mass, and in addition ethylbenzene.
23. With $\geq 19\%$ diluent type A by mass, and in addition methyl isobutyl ketone.
24. Diluent type B with boiling point >100 C.
25. No "Corrosive" subsidiary risk label is required for concentrations below 56%.
26. Available oxygen must be $\leq 7.6\%$.

27. Formulations derived from distillation of peroxyacetic acid originating from peroxyacetic acid in a concentration of not more than 41% with water, total active oxygen less than or equal to 9.5% (peroxyacetic acid plus hydrogen peroxide).

28. For the purposes of this section, the names "Peroxyacetic acid" and "Peracetic acid" are synonymous.

(d) *Packing Method Table*. Packagings for organic peroxides and self-reactive substances are listed in the Maximum Quantity per Packing Method Table. The packing methods are designated OP1 to OP8. The quantities specified for each packing method represent the maximum that is authorized.

(1) The following types of packagings are authorized:

(i) Drums: 1A1, 1A2, 1B1, 1B2, 1D, 1G, 1H1, 1H2;

(ii) Jerricans: 3A1, 3A2, 3B1, 3B2, 3H1, 3H2;

(iii) Boxes: 4C1, 4C2, 4D, 4F, 4G, 4H1, 4H2, 4A, 4B; or

(iv) Composite packagings with a plastic inner receptacle: 6HA1, 6HA2, 6HB1, 6HB2, 6HC, 6HD1, 6HD2, 6HG1, 6HG2, 6HH1, 6HH2.

(2) Metal packaging (including inner packagings of combination packagings and outer packagings of combination or composite packagings) are used only for packing methods OP7 and OP8.

(3) In combination packagings, glass receptacles are used only as inner packagings with a maximum content of 0.5 kg for solids or 0.5 L for liquids.

(4) The maximum quantity per packaging or package for Packing Methods OP1–OP8 must be as follows:

Maximum Quantity Per Packaging/Package

[For Packing Methods OP1 to OP8]

Maximum quantity	Packing Method							
	OP1	OP2	OP3	OP4 ¹	OP5	OP6	OP7	OP8
Solids and combination packagings (liquid and solid) (kg)	0.5	0.5/10	5	5	25	50	50	2400
Liquids (L)	0.5		5		30	60	60	3225

¹If two values are given, the first applies to the maximum net mass per inner packaging and the second to the maximum net mass of the complete package.

²60 kg for jerricans/200 kg for boxes and, for solids, 400 kg in combination packagings with outer packagings comprising boxes (4C1, 4C2, 4D, 4F, 4G, 4H1, and 4H2) and with inner packagings of plastics or fiber with a maximum net mass of 25 kg.

³60 L for jerricans.

(e) *Organic Peroxide IBC Table*. The following Organic Peroxide IBC Table specifies, by technical name, those organic peroxides that are authorized for transportation in certain IBCs and not subject to the approval provisions of §173.128 of this part. Additional requirements for authorized IBCs are found in paragraph (f) of this section.

Organic Peroxide IBC Table



UN No.	Organic peroxide	Type of IBC	Maximum quantity (litres)	Control temperature	Emergency temperature
3109	ORGANIC PEROXIDE, TYPE F, LIQUID				
	tert-Butyl hydroperoxide, not more than 72% with water	31A	1250		
	tert-Butyl peroxyacetate, not more than 32% in diluent type A	31A	1250		
		31HA1	1000		
	tert-Butyl peroxy-3,5,5-trimethylhexanoate, not more than 32% in diluent type A	31A	1250		
		31HA1	1000		
	Cumyl hydroperoxide, not more than 90% in diluent type A	31HA1	1250		
	Dibenzoyl peroxide, not more than 42% as a stable dispersion	31H1	1000		
	Di-tert-butyl peroxide, not more than 52% in diluent type B	31A	1250		
		31HA1	1000		
	1,1-Di-(tert-butylperoxy) cyclohexane, not more than 42% in diluent type A	31H1	1000		
	Dicumyl peroxide, less than or equal to 100%	31A	1250		
		31HA1	1000		
	Dilauroyl peroxide, not more than 42%, stable dispersion, in water	31HA1	1000		
	Isopropyl cumyl hydroperoxide, not more than 72% in diluent type A	31HA1	1250		
	p-Menthyl hydroperoxide, not more than 72% in diluent type A	31HA1	1250		
	Peroxyacetic acid, stabilized, not more than 17%	31H1	1500		
		31HA1	1500		
		31A	1500		
	Peroxyacetic acid, with not more than 26% hydrogen peroxide	31A	1500		
		31HA1	1500		
	Peroxyacetic acid, type F, stabilized	31A	1500		
		31HA1	1500		
3110	ORGANIC PEROXIDE TYPE F, SOLID				
	Dicumyl peroxide, less than or equal to 100%	31A	2000		
		31H1			
		31HA1			

3119	ORGANIC PEROXIDE, TYPE F, LIQUID, TEMPERATURE CONTROLLED				
	tert-Butyl peroxy-2-ethylhexanoate, not more than 32% in diluent type B	31HA1	1000	+30 °C	+35 °C
		31A	1250	+30 °C	+35 °C
	tert-Butyl peroxyneodecanoate, not more than 32% in diluent type A	31A	1250	0 °C	+10 °C
	tert-Butyl peroxyneodecanoate, not more than 42% stable dispersion, in water	31A	1250	-5 °C	+5 °C
	tert-Butyl peroxy-pivalate, not more than 27% in diluent type B	31HA1	1000	+10 °C	+15 °C
		31A	1250	+10 °C	+15 °C
	Cumyl peroxyneodecanoate, not more than 52%, stable dispersion, in water	31A	1250	-15 °C	-5 °C
	Dicyclohexylperoxydicarbonate, not more than 42% as a stable dispersion, in water	31A	1250	+10 °C	+15 °C
	Di-(4-tert-butylcyclohexyl) peroxydicarbonate, not more than 42%, stable dispersion, in water	31HA1	1000	+30 °C	+35 °C
	Dicetyl peroxydicarbonate, not more than 42%, stable dispersion, in water	31HA1	1000	+30 °C	+35 °C
	Di-(2-ethylhexyl) peroxydicarbonate, not more than 52%, stable dispersion, in water	31A	1250	-20 °C	-10 °C
	Dimyristyl peroxydicarbonate, not more than 42%, stable dispersion, in water	31HA1	1000	+15 °C	+20 °C
	Di-(3,5,5-trimethylhexanoyl) peroxide, not more than 38% in diluent type A	31HA1	1000	+10 °C	+15 °C
		31A	1250	+10 °C	+15 °C
	Di-(3,5,5-trimethylhexanoyl) peroxide, not more than 52%, stable dispersion, in water	31A	1250	+10 °C	+15 °C
	1,1,3,3-Tetramethylbutyl peroxyneodecanoate, not more than 52%, stable dispersion, in water	31A	1250	-5 °C	+5 °C

(f) IBCs. IBCs are authorized subject to the conditions and limitations of this section if the IBC type is authorized according to paragraph (e) of this section, as applicable, and the IBC conforms to the requirements in subpart O of part 178 of this subchapter at the Packing Group II performance level. Type F organic peroxides or self-reactive substances are not authorized for transportation in IBCs other than those specified, unless approved by the Associate Administrator.

(1) IBCs shall be provided with a device to allow venting during transportation. The inlet to the pressure relief device shall be sited in the vapor space of the IBC under maximum filling conditions during transportation.

(2) To prevent explosive rupture of metal IBCs or composite IBCs with a complete metal casing, the emergency-relief devices shall be designed to vent all the decomposition products and vapors evolved during self-accelerating decomposition or during a period of not less than one hour of complete fire-engulfment as calculated by the formula in paragraph (h)(3)(v) of this section. The control and emergency temperatures specified in the Organic Peroxide IBC Table are based on a non-insulated IBC.

(g) Organic Peroxide Portable Tank Table. The following Organic Peroxide Portable Tank Table provides certain portable tank requirements and identifies, by technical name, those organic peroxides that are authorized for transportation in the bulk packagings

listed in paragraph (h). Organic peroxides listed in this table, provided they meet the specific packaging requirements found in paragraph (h), are not subject to the approval provisions of §173.128 of this part.

Organic Peroxide Portable Tank Table

UN No.	Hazardous material	Minimum test pressure (bar)	Minimum shell thickness (mm-reference steel) See...	Bottom opening requirements See...	Pressure-relief requirements See...	Filling limits	Control temperature	Emergency temperature
3109	ORGANIC PEROXIDE, TYPE F, LIQUID							
	tert-Butyl hydroperoxide, not more than 72% with water *Provided that steps have been taken to achieve the safety equivalence of 65% tert-Butyl hydroperoxide and 35% water	4	§178.274 (d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	Cumyl hydroperoxide, not more than 90% in diluent type A	4	§178.274 (d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	Di-tert-butyl peroxide, not more than 32% in diluent type A	4	§178.274 (d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	Dicumyl peroxide, less than or equal to 100% in diluent type B	4	§178.274 (d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	Isopropyl cumyl hydroperoxide, not more than 72% in diluent type A	4	§178.274 (d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		

	p-Menthyl hydroperoxide, not more than 72% in diluent type A	4	§178.274(d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	Pinanyl hydroperoxide, not more than 56% in diluent type A	4	§178.274(d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
3110	ORGANIC PEROXIDE, TYPE F, SOLID							
	Dicumyl peroxide less than or equal to 100% with inert solids *Maximum quantity per portable tank 2,000 kg	4	§178.274(d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
3119	ORGANIC PEROXIDE, TYPE F, LIQUID, TEMPERATURE CONTROLLED							
	tert-Butyl peroxyacetate, not more than 32% in diluent type B	4	§178.274(d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	+30 °C	+35 °C
	tert-Butyl peroxy-2-ethylhexanoate, not more than 32% in diluent B	4	§178.274(d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	+15 °C	+20 °C
	tert-Butylperoxypivalate, not more than 27% in diluent type B	4	§178.274(d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	+5 °C	+10 °C
	tert-Butyl peroxy-3,5,5-trimethylhexanoate, not more than 32% in diluent type B	4	§178.274(d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	+35 °C	+40 °C

Di-(3,5,5-trimethylhexanoyl) peroxide, not more than 38% in diluent type A	4	§178.274(d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	0 °C	+5 °C
Peroxyacetic acid, distilled, stabilized, not more than 41%	4	§178.274(d)(2)	§178.275(d)(3)	§178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	+30 °C	+35 °C

(h) *Bulk packagings other than IBCs.* The following bulk packagings are authorized, subject to the conditions and limitations of this section, if the organic peroxide is listed in the Organic Peroxide Portable Tank Table and bulk packagings are authorized, or if the organic peroxide is specifically authorized for transport in a bulk packaging by this paragraph (h), and the bulk packaging conforms to the requirements of this subchapter:

(1) *Rail cars.* Class DOT 103, 104, 105, 109, 111, 112, 114, 115, or 120 fusion-weld tank car tanks are authorized. DOT 103W, 111A60F1 and 111A60W1 tank car tanks must have bottom outlets effectively sealed from inside. Gauging devices are required on DOT 103W tank car tanks. Riveted tank car tanks are not authorized.

(2) *Cargo tanks.* Specification MC 307, MC 310, MC 311, MC 312, DOT 407, and DOT 412 cargo tank motor vehicles with a tank design pressure of at least 172 kPa (25 psig) are authorized.

(3) *Portable tanks.* The following requirements apply to portable tanks intended for the transport of organic peroxides or self-reactive substances. DOT 51, 57, IM 101 portable tanks, and UN portable tanks that conform to the requirements of paragraph (g) of this section, are authorized. Type F organic peroxide or self-reactive substance formulations other than those indicated in the Organic Peroxide Portable Tank Table may be transported in portable tanks if approved by the Associate Administrator. The following conditions also apply:

(i) The portable tank must be designed for a test pressure of at least 0.4 MPa (4 bar).

(ii) The portable tank must be fitted with temperature-sensing devices.

(iii) The portable tank must be fitted with pressure relief devices and emergency-relief devices. Vacuum-relief devices may also be used. Pressure relief devices must operate at pressures determined according to both the properties of the hazardous material and the construction characteristics of the portable tank. Fusible elements are not allowed in the shell.

(iv) The pressure relief devices must consist of reclosing devices fitted to prevent significant build-up within the portable tank of the decomposition products and vapors released at a temperature of 50 °C (122 °F). The capacity and start-to-discharge pressure of the relief devices must be in accordance with the applicable requirements of this subchapter specified for the portable tank. The pressure relief devices must not allow liquid to escape in the event the portable tank is overturned in a loaded condition.

(v)(A) The emergency-relief devices may be of the reclosing or frangible types, or a combination of the two, designed to vent all the decomposition products and vapors evolved during a period of not less than one hour of complete fire engulfment as calculated by the following formula:

$$q=70961 F A^{0.82}$$

Where:

q = heat absorption (W)

A = wetted area (m²)

F = insulation factor (-)

(B) Insulation factor (F) in the formula in paragraph (h)(3)(v)(A) of this section equals 1 for non-insulated vessels and for insulated vessels F is calculated using the following formula:

$$F = \frac{U (923 - T_{PO})}{47032}$$

Where:

U = K/L = heat transfer coefficient of the insulation (W·m⁻²·K⁻¹); where K = heat conductivity of insulation layer (W·m⁻¹·K⁻¹), and L = thickness of insulation layer (m).

T_{PO} = temperature of material at relieving conditions (K).

(vi) The start-to-discharge pressure of emergency-relief devices must be higher than that specified for the pressure relief devices in paragraph (h)(3)(iv) of this section. The emergency-relief devices must be sized and designed in such a way that the maximum pressure in the shell never exceeds the test pressure of the portable tank.

Note to paragraph(h)(3)(vi): An example of a method to determine the size of emergency-relief devices is given in Appendix 5 of the UN Manual of Tests and Criteria (IBR, see §171.7 of this subchapter). A second example of a test method for venting sizing is given in the American Institute of Chemical Engineers Process Safety Progress Journal, June 2002 issue (Vol. 21, No. 2) (Informational materials not requiring incorporation by reference, see §171.7(b)).

(vii) For insulated portable tanks, the capacity and setting of emergency-relief devices must be determined assuming a loss of insulation from 1% of the surface area.

(viii) Vacuum-relief devices and reclosing devices on portable tanks used for flammable hazardous materials must be provided with flame arresters. Any reduction of the relief capacity caused by the flame arrester must be taken into account and the appropriate relief capacity must be provided.

(ix) Service equipment such as devices and external piping must be designed and constructed so that no hazardous material remains in them after filling the portable tank.

(x) Portable tanks may be either insulated or protected by a sun-shield. If the SADT of the hazardous material in the portable tank is 55 °C (131 °F) or less, the portable tank must be completely insulated. The outer surface must be finished in white or bright metal.

(xi) The degree of filling must not exceed 90% at 15 °C (59 °F).

(xii) DOT 57 metal portable tanks are authorized only for those materials or mixtures of two or more materials that are provided with a reference to Note 9 in Column 8 of the Organic Peroxide Table, found in paragraph (c) of this section. DOT 57 portable tanks must conform to the venting requirements of paragraph (f) of this section. These portable tanks are not subject to any other requirements of paragraph (h) of this section.

(4) For tertiary butyl hydroperoxide (TBHP), each tank car, cargo tank or portable tank must contain 7.6 cm (3.0 inches) low density polyethylene (PE) saddles having a melt index of at least 0.2 grams per 10 minutes (for example see, ASTM D1238, condition E) as part of the lading, with a ratio of PE to TBHP over a range of 0.008 to 0.012 by mass. Alternatively, plastic or metal containers equipped with fusible plugs having a melting point between 69 °C (156 °F) and 71 °C (160 °F) and filled with a sufficient quantity of water to dilute the TBHP to 65% or less by mass may be used. The PE saddles must be visually inspected after each trip and, at a minimum, once every 12 months, and replaced when discoloration, fracture, severe deformation, or other indication of change is noted.